## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LEDmaxx GmbH

Supplier's address: LEDmaxx GmbH, Wiesenweg 2 97353 Wiesentheid

## Model identifier: A22F04C

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

rioduct parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 00 h), rounded st integer	5	Energy efficiency class	F		
indicating if it rain a sphere (30	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	540 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200		
On-mode p expressed in W	oower (P <sub>on</sub> ),	5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	108	Spectral power	See image		
dimensions	Width	60	distribution in the	in last page		
without	Depth	60	1	Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	44			
		Chromaticity coordinates (x and y)	0,463 0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,40	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-' : not applicable;

(b)'\_-' : not applicable;

